



R730H
HIGH EFFICIENCY
CART & UTENSIL WASHER

www.nsc-betterbuilt.com



R730H HIGH EFFICIENCY CART & UTENSIL WASHER

The BetterBuilt R730H Cart & Utensil Washer reflects the current desire for high efficiency equipment which consumes less energy, increases productivity and promises sustainability for the future.

Oscillating Manifold Spray Jet System

Wash and rinse solutions are distributed throughout the wash chamber via 110 degree oscillating arms mounted horizontally along the sidewalls of the chamber. These spray jet manifolds with 160 wash nozzles and 100 rinse nozzles provide complete coverage.

Touchscreen Control Systems

A microcomputer with 8" TFT color touchscreen interface monitors and controls all aspects of the washer cycles and process operations. Unique features include adjustable multi-tiered password access, advanced diagnostics, alarm and data logging, parts list ID with visual reference assists maintenance and troubleshooting.

Maintenance and Replacement Parts

A preventative maintenance program is required for warranty purposes and is available from a local service agent. All BetterBuilt washers use microprocessor program controllers for long life and ease of service diagnostics. All components are non-proprietary and are available from local suppliers or the factory.

Alkaline and Acid Compatible

All BetterBuilt washers have a stainless steel cabinet and circulatory system, containing no plastic or rubber connections. This makes the washer compatible with all alkaline or acidic detergents and extends the operational life of the washer.

Safety Features

Personnel safety features include an emergency stop (e-stop) button located at each door. Inside the wash chamber, two highly visible emergency stop cables are located on both sides. The washer is equipped with a mechanical over-pressurization relief system.

Inflatable Door Gasket

Each door is equipped with a dual heavy-duty pneumatic lock and EPDM inflatable gasket to completely seal the cabinet door.





Fast Cycle Times Low Water Consumption

Separate heated and insulated storage tanks for wash and rinse solutions provide cycle times of 6 – 9 minutes for an alkaline wash and 10 – 15 minutes for an acid wash. By returning wash solution to the storage tank and reusing it for the next wash cycle, less energy, water and chemicals are consumed.

Aqua Pulse Spray

Spray emphasis from either side of the wash chamber is adjustable for duration and modulation frequency from side to side which optimizes chemical and water pressure performance during either the wash and/or rinse stage of a cycle.

Low-Profile Base

The 6" base allows the washer to be placed in a shallow pit or be floor mounted.

Reduce Cross Contamination

The washer sump is fully drained with a fresh water flush at the end of every rinse step. Dedicated piping for the wash and rinse solutions is also designed to reduce cross contamination.

Self Cleaning Filter

The double layer, 60 mesh, stainless steel automatic self-cleaning filter is located on the load side of the washer behind a lockable service door for easy access.

Load Bumper Rails

The washer chamber is provided with side rails and radius curbs which help center racks and protect the oscillating spray arms from damage during loading and unloading of the washer.

Optional Closed Circuit TV Camera

The 8" touch screen is capable of 32,000 colors of resolution which is perfect for an integral CCTV camera allowing operators on the loading side of the washer to view the clean side wash room area. Up to 4 CCTV cameras can be integrated into the touch screen controls package.



R700 SERIES HIGH EFFICIENCY CART & UTENSIL WASHER

APPLICATION

The BetterBuilt R730H Washer is an automatic, heavy duty, multi-cycle, single chamber, floor loading, hydro-spray washer using an oscillating high-pressure spray system with heated, insulated solution storage tanks for fast cycle times, low utilities consumption and complete coverage.

INTERIOR CHAMBER

W x H x L

EXTERIOR CABINET

W x H x L

MODEL

R730H

48 x 88 x 90"
1219 x 2235 x 2286mm

92 x 108 x 97.5"
2337 x 2743 x 2477mm

Note: Due to continued engineering improvements, specifications are subject to change without notice.

STANDARD FEATURES

- Single Door Cabinet
- Pit Mounted or Floor Mounted, Low Profile 6" Base
- All Stainless Steel Construction
- Insulated Double Wall Cabinet and Door
- Manual Swing-out, Hinged Door
- Inflatable Door Gasket for Positive Seal
- Air Piston Door Lock
- Stainless Steel Perforated Floor in Lift-up Sections
- Stainless Steel Pump and Circulatory Piping
- Stainless Steel Tank Steam Coil Heating
- Automatic Tank Level Control
- Stainless Steel Heated Alkaline and Final Rinse Tanks
- Oscillating Manifold Spray Jet System
- Dedicated Wash and Final Rinse Piping, No Cross Contamination
- Adjustable Spray Patterns
- Temperature Guarantee During All Cycle Phases
- Automatic Self-Cleaning Filter System
- Drain Discharge Cool Down
- Interior Bumper Rails, Radius Curbs
- Chemical Injection Ports, Contacts and Fittings
- Pneumatic Operated Exhaust Damper
- Illuminated Chamber Interior
- Automatic Multi Phase Treatment Cycles
- Multi-cycle Microprocessor Control System
- 8 Fully Adjustable Programmed Cycles
- 8" TFT Color Touchscreen Control Panel
- Stainless Steel Control Guard
- Program Security via Pin Number Access
- Built-in Advanced Diagnostics
- Interior Emergency Stop Cable on Both Sides
- Emergency Stop Button at Door
- Service Side Exterior Stainless Steel Panels
- Non-proprietary Components

OPTIONAL FEATURES

- Double Door Pass Thru Cabinet
- Left or Right Side Service Access
- Barrier Wall Trim to Close Wall Openings
- Seismic Anchoring
- Water Supply Temperature Booster
- Vapour Removal Condenser
- Power Exhaust Stainless Steel Blower
- Convection Air Dryer System
- Automatic Chemical Injection Pumps, Time Based
- Low Level Chemical Sensor
- Sampling Port
- Direct Facility Rinse
- Ethernet Connectivity to PLC or Touchscreen
- Factory Ethernet Connectivity for Online Diagnostics
- Modem Connectivity for Factory Diagnostics
- PLC and Touchscreen Program Backup
- Compact Flash Card for Data Collection
- RS485 Port for Data Download
- Impact or Thermal Cycle Data Printer
- Printer Cover
- CCTV Capability for Unload Side Camera
- Surge Protection
- Clean Side Buzzer
- Knocked Down Shipment
- Automatic Tilt Floor

ACCESSORIES

UWC-6 Utensil Washing Cart - Acart UW100

CWC-6 Container Washing Cart - Acart UW101-4

DIVISION OF NORTHWESTERN SYSTEMS CORP

7601 MacDonald Road • Delta, British Columbia • Canada V4G 1N3

888-553-0855 • Tel: 604-952-0925 • Fax: 604-952-0941

www.nsc-betterbuilt.com • info@nsc-betterbuilt.com